



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

Preconsolidation Pressure and Creep Settlements

estimations based on results of oedometer tests

Thorsen, Grete

Published in:

Proceedings of the International Symposium on Compression and Consolidation of Clayey Soils

Publication date:
1995

Document Version
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Thorsen, G. (1995). Preconsolidation Pressure and Creep Settlements: estimations based on results of oedometer tests. In H. Yoshikuni, & O. Kusakabe (Eds.), *Proceedings of the International Symposium on Compression and Consolidation of Clayey Soils: IS-Hiroshima '95, May 1995* (Vol. 1, pp. 287-292). CRC Press/Balkema.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

PROCEEDINGS OF THE INTERNATIONAL SYMPOSIUM ON COMPRESSION AND
CONSOLIDATION OF CLAYEY SOILS – IS-HIROSHIMA '95/JAPAN/10-12 MAY 1995

Compression and Consolidation of Clayey Soils

Edited by

HIROSHI YOSHIKUNI & OSAMU KUSAKABE

Department of Civil Engineering, Hiroshima University, Japan

OFFPRINT



A.A. BALKEMA/ROTTERDAM/BROOKFIELD/1995

Preconsolidation pressure and creep settlements – Estimations based on results of oedometer tests

Grete Thorsen

Aalborg University, Denmark

ABSTRACT: The paper describes results of geotechnical investigations carried out in order to estimate the state of consolidation in Holocene silt and clay sediments of unusual thickness. The clay and silt sediments are overlain by 30 meters of sand, sedimented within the latest 1000 years.

Results of oedometer tests with undisturbed samples have been analysed by means of different methods to determine the preconsolidation pressure.

An attempt is made to estimate the creep rates on the basis of AMS ^{14}C -datings of the sediments and a model for creep determination proposed by Moust Jacobsen.

1 INTRODUCTION

The top of Denmark is a spit, Skaw Spit (Skagen Odde), formed since the Weichselian Ice Age by marine sediments. The outermost part of the spit emerged during the latest few centuries.




Fig. 1. The changing position of the northernmost coastline of the Skaw Spit (Hauerbach, 1992).

Levellings have indicated, that the youngest part of the spit does not follow the general geostatic uplift of the northern part of Denmark (Hauerbach, 1992).

Further, geological and geophysical investigations have indicated an unusual thickness of relatively young sediments (Knudsen, 1985, Lykke-Andersen, 1987).

In 1992 a boring, Skagen 3, was carried out at the very point of the spit, The Grenen Point. The boring was taken to a depth of 220 m and has shown 114 m of Holocene sediments underlain by sediments from Weichselian, Eemian, Saalian and Lower Cretaceous (Knudsen, 1994).



Fig. 2. The position of Skagen 3 boring.

The material from the boring is being studied as a research project by the GeoKat group at the Department of Earth Sciences, University of Aarhus in cooperation with "The Skagen Spit project -nature and culture", The Geological Survey of Denmark, The University of Quebec in Montreal, The University of Cambridge and Aalborg University.

One of the purposes of the geotechnical investigations presented in this paper has been to estimate the state of consolidation of the Holocene sediments.




Fig. 3. Skagen 3 boring (Knudsen, 1994).

2. SAMPLING AND IN SITU TESTING

The Skagen 3 boring was, from the depth of 30 m, carried out as a rotary boring with continuous coring. In the Holocene silt and clay layers, undisturbed 70 mm diameter samples were extracted and vane tests carried out at 3 to 6 meters intervals.

In 1993 a boring, Skagen 4, through the upper 30 m "Odde"sand, was carried out as a cable percussion boring with continuous Split Spoon sampling.

In the Holocene clay sediments the undrained shear strength, c_v , measured by the vane represents values of 0.2 to 0.25 times the in situ pressure, σ'_o .

Based on the statistical relation $c_u / \sigma'_o = 0.11 + 0.0037 I_p$, (Skempton, 1957), and the determined values of plasticity index, I_p , (chapt. 3), the results may indicate a clay in a normally consolidated state.




Fig. 4. Skagen 3 boring. Undrained shear strength measured by vane.

3. LABORATORY TESTING

Classification tests and oedometer tests have been carried out with the majority of the undisturbed samples from the Holocene sediments and also with a few samples of the cores from Weichselian and Eemian.

Results of the determination of water content, w , Atterberg limits, w_L and w_p , plasticity index, I_p , and organic content, O.C., are shown in Fig. 5.




Fig. 5. Skagen 3 boring. Water content, Atterberg limits, plasticity index and organic content.

The oedometer tests have been carried out with 60 mm diameter samples in The Danish Consolidation Apparatus, which has a floating ring (Moust Jacobsen, 1967). The registration of the deformations during the tests has been automatic and continuous using transducers with an accuracy of 10^{-3} mm. The main results of the oedometer tests are given in fig. 6.




Fig. 6. Skagen 3 boring. Results of oedometer tests.

$Q = \frac{C_c}{(1+e_0)}$, C_c is the coefficient of compressibility
 $Q_s = de/d \log t$, the creep rate for a soil in a normally consolidated state.

The values of Q_s/Q correspond to the values found by Mesri (Mesri, 1987).

For the Holocene clay the coefficient of consolidation, c_k , has been determined to $4 - 8 \times 10^{-8} m^2/sec$.

4. DETERMINATION OF PRECONSOLIDATION PRESSURE FROM OEDOMETER TESTS

On the basis of the oedometer tests the preconsolidation pressure of the soil has been determined using methods as suggested by Casagrande, Akai, and Christensen and Janbu.

4.1 Casagrande's method

For many years the method described by Casagrande (Casagrande, 1936) has been commonly used for the determination of the preconsolidation pressure from results of oedometer tests.




Fig. 7. Casagrande's method.




Fig. 8. Skagen 3 boring. Determination of σ'_{pc} by Casagrande's method.

4.2 Akai's method

Akai (Akai, 1960) has used the variation in the creep rate to determine the preconsolidation pressure.

A time settlement curve from a loading can be divided into a consolidation phase and a creep phase. The creep is assumed to be logarithmic by time having a creep rate of ϵ_s .

Akai discovered, that the rate of creep increased proportionally with the effective stress, σ' , for $\sigma' < \sigma'_{pc}$ and with $\log \sigma'$ when $\sigma' > \sigma'_{pc}$.




Fig. 9. Akai's method.

In the actual tests ϵ_s has proved to be nearly constant, Q_s , for $\sigma' > \sigma'_{pc}$.




Fig. 10. Skagen 3 boring. Determination of σ'_{pc} by Akai's method.

4.3 Christensen and Janbu's methods

Christensen and Janbu (Christensen and Janbu, 1992), have suggested two methods to determine the preconsolidation pressure.

1) It is possible to determine the preconsolidation pressure from the variation in the Modulus $K = d\sigma'/d\epsilon$. For a preconsolidated soil the modulus is nearly constant and for a normally consolidated soil the variation in the modulus is linear to the stress. It is therefore possible to determine σ'_{pc} at the break in the curve for modulus against stress.




Fig. 11. Skagen 3 boring. Holocene clay. Curves for a) stress - strain b) modulus - stress.

2) The time resistance $R = dt/de$ from a time-settlement curve plotted against time will after some time show a linear curve. The inclination of this line $r = dR/dt$ against stress for each load step will show a break in the curve at σ'_{pc} .




Fig. 12. Skagen 3 boring. Holocene clay. Curves for a) R against time b) r against stress.




Fig. 13. Skagen 3 boring. Determination of σ'_{pc} by Christensen and Janbu's methods.

4.4 Results of the determination of σ'_{pc}

The results of the determinations of the pre-consolidation pressures as described above indicate the overconsolidation ratio for the Late Glacial and Holocene clays to be $OCR \geq 1$.

In a stepwise oedometer test carried out on samples with in situ pressures as high as in the actual case, it is difficult to determine the correct value of σ'_{pc} because of the size of the load increment in each step. The scattering in the values determined may therefore represent the uncertainties in the determinations rather than variations in the preconsolidation pressures.

The boring has shown clay from 80 m to 134 m, which means a maximum drainage path of 27 m. On the basis of the determined coefficient of

consolidation, c_k , the corresponding time of consolidation is 500 - 1000 years.

In the Late Glacial sediments sand and silt stripes have been observed, which may reduce the drainage path to 17 m and the time of consolidation to 200 - 500 years.

The results of the oedometer tests have indicated that the consolidation process in the Holocene and Late Glacial sediments, caused by the sedimentation of the "Odde"sand, is completed. Based on this it is concluded, that the drainage path must be smaller than half the total thickness of the clay sediments and that the sedimentation of the "Odde"sand must have been nearly finished some hundred years ago.

For the sample extracted just below the upper till layer and for the sample from Eemian the preconsolidation pressures have been determined to more than 2000 kPa and more than 4000 kPa, respectively, corresponding to $OCR \geq 1.4$ and $OCR \geq 2.3$.

5. AGE OF THE SEDIMENTS IN SKAGEN 3

Samples of foraminifera and shells from the marine sediments have been radiocarbon dated by the Accelerator Mass Spectrometry (AMS), (Nielsen et al., 1994). Results from these datings have shown the age of the Holocene clay and silt sediments to be about 12.000 years in 114 m, about 6.000 years in 80 m and about 1000 years in 30 m below the surface.

The rate of sedimentation has been rather uniform, until the start of the sedimentation of the "Odde"sand.

Fig. 14. shows the max. and min. values of the datings from the "Odde"sand. In the upper 12 m of the sand there are no datings because of lack of shells and foraminifera.




Fig. 14. Skagen 3 boring. Results of AMS ^{14}C -datings from the "Odde"sand (Nielsen et al., 1994).

6. CREEP

6.1 Moust Jacobsen's model

Moust Jacobsen (Moust Jacobsen, 1992) has set up a model to separate creep and consolidation deformations during the consolidation process.

Moust Jacobsen assumed the consolidation and creep to be simultaneous, and has described the creep as

$$\epsilon_{cr} = Q_s \log\left(1 + \frac{t_r}{t_b}\right) \quad (1)$$

Q_s = rate of creep for $\sigma' \geq \sigma'_{pc}$

t_r is the real time passed

t_b is a reference time

If the sample is under constant stress from a time t_A to a time $t_A + t$, the additional creep is

$$\Delta\epsilon_{cr} = Q_s \log\left(1 + \frac{t}{t_A + t_b}\right) \quad (2)$$

and

$$\Delta\epsilon_{cr} \sim Q_s \log\left(1 + \frac{t}{t_A}\right) \text{ if } t_A \gg t_b$$




Fig. 15. Behavior of slightly preconsolidated clay (Bjerrum, 1967).

t_A is the creep age, an age which will be reduced by any new loading (Bjerrum, 1967).

For a normally consolidated soil the creep age has often been assumed to be the geological age.

6.2 Creep deformations

In a curve described by (1), t_b is seen to be the additional time which turns the curve into a straight line in a logarithmic scale. t_b might therefore represent the creep time during the consolidation process, and the minimum value for t_A if the consolidation process is completed.

Assuming that the high sedimentation rate of the "Odde"sand from AD 1000 to AD 1200 has reduced the creep age to zero, corresponding to a creep age today of about 800 years the present creep rate is less than:

$$\Delta\epsilon_{cr} = Q_s \log\left(1 + \frac{1}{800}\right) = Q_s \times 5,4 \times 10^{-4}\%$$

which gives a creep rate of about 0.2 mm/year for the total Holocene layer.

If the creep age is reduced to only 300 years, the creep rate is less than 0.5 mm/year.

Many uncertainties about creep still exist, and especially about the correspondence between the values determined in the laboratory and the real values.

Moust Jacobsen's model makes it possible to separate creep and consolidation by subtraction of the creep curve from the time settlement curve in the laboratory tests. Consequently the determination of the primary curve is improved and a value for the creep age for every load step is obtained. Based on this, an estimation of the state of consolidation is possible.

The actual oedometer tests have been carried out with the additional purpose to study the creep deformations and further investigations of the actual oedometer tests are in progress.




Fig. 16. Separation of creep and consolidation for a soil in a normally consolidated state.

7. CONCLUSION

The results of the geotechnical investigations in the Skagen 3 boring have indicated that the consolidation process in the Holocene silt and clay sediments caused by the sedimentation of the "Odde"sand is completed.

Based on an $OCR \geq 1$ and the values of the coefficient of consolidation, c_v , determined in the laboratory for the samples of clay, it is further concluded, that the actual drainage path in the clay sediments is smaller than half the total thickness of the clay deposits and that the sedimentation of the "Odde" sand must have been nearly finished some hundred years ago.

The AMS ^{14}C -datings have shown a very rapid sedimentation of the lower 18 m of the "Odde" sand. Datings of the upper 12 m sand are necessary to improve the modelling of the consolidation process.

The size of the creep rate is very dependent on the creep age and many uncertainties still exist about the correspondence between the values determined in the laboratory and the real values.

Moust Jacobsen (Moust Jacobsen, 1992) has set up a model to separate creep and consolidation in the laboratory tests. Based on this model further investigations of the actual oedometer tests are in progress in an attempt to improve the understanding of creep.

REFERENCES

- Akai, K. 1960. *Die structurellen Eigenschaften von Schluff*. Mitteilungen Heft 22. Die Technische Hochschule, Aachen.
- Bjerrum, L. 1967. Engineering Geology of the Norwegian Normally Consolidated Marine Clays as Related to Settlements of Buildings. *Geotechnique* 17, p. 81 - 118.
- Casagrande, A. 1936. The determination of the preconsolidation pressure and its significance. *IICSMFE* Cambridge, Vol. 3, p. 60 - 64.
- Christensen, S., Janbu, N. 1992. Ødometerforsøg - et primærkrav i praktisk geoteknik. (Oedometer tests - a primary requirement in practical soil mechanics). *Proc. NGM-92*, Aalborg, Danish Geotechnical Society, Bulletin 9, Vol. 2, p. 449 - 454.
- Hauerbach, P. 1992. Skagen Odde - The Skaw Spit - an area of land created between two seas. *Folia Geographica Danica*. Tom XX. Copenhagen: Reitzel.
- Knudsen, K. L. 1985. Correlation of Saalian, Eemian and Weichselian foraminiferal zones in North Jutland. *Bulletin of the Geological Society of Denmark*, 33, p. 325 - 329.
- Knudsen, K. L. 1994. The marine Quarternary in Denmark: a review of new evidence from glacial-interglacial studies. *Bulletin of the Geological Society of Denmark*, 41, in press.
- Lykke-Andersen, H. 1987. Thickness of Quaternary deposits and their relation to the pre-Quaternary in the Fennoscandian border zone in Kattegat and Vendsyssel. *Boreas*, 16, p. 369 - 371.
- Mesri, G., Asce, M. & A. Castro 1987. C_α/C_c Concept and K_o during secondary compression. *Journal of Geotechnical Engineering*, Vol. 113, No. 3, p. 230 - 247.
- Moust Jacobsen, H. 1967. *Morænelers geotekniske Egenskaber*. (The geotechnical properties of clay till). Ph. D.-thesis 1967. Reprinted 1994. Aalborg University.
- Moust Jacobsen, H. 1992. Bestemmelse af forbelastningsstryk i laboratoriet. (Determination of preconsolidation pressure in the laboratory). *Proc. NGM-92*, Aalborg, Danish Geotechnical Society, Bulletin 9, Vol. 2, p. 455 - 460.
- Moust Jacobsen, H. 1992. Karakteristiske belastningstilstande for moræneler. (Characteristic stress conditions for clay till). *Proc. NGM-92*, Aalborg, Danish Geotechnical Society, Bulletin 9, Vol. 2, p. 461 - 466.
- Nielsen, S. H., Conradsen, K., Heinemeier, J., Knudsen, K. L., Nielsen, H. L., Rud, N. & A. E. Sveinbjörnsdóttir 1994. Radiocarbon dating of shells and foraminifera from the Skagen core, Denmark: Evidence of reworking. 15th International Radiocarbon Conference, Glasgow.
- Skempton, A. W. 1957. "Discussion: The planning and design of the new Hong Kong airport." *Proc. Inst. Civil Engrs.*, London, 7, p. 305 - 307.

FROM THE SAME PUBLISHER:

Ortigao, J.A.R. 90 5410 194 6
Soil mechanics in the light of critical state theories:

An introduction

1995, 25 cm, 160 pp., Hfl.120/\$65.00/£45

(Student edn., 90 5410 195 4, Hfl.70/\$35.00/£31)

Reviews soil mechanics in the light of critical state soil mechanics, developed at the University of Cambridge, England in the late sixties. Critical state concepts gained widespread recognition as a framework to the understanding of the behaviour of soils. The same model is applicable to different materials such as sands and clays. Essentially the text is divided into 14 chapters. A number of exercises, both solved (62) and proposed (106), are presented. A microcomputer program named *Cris* accompanies the book. It is used for training and simulation of the behaviour of soil samples subjected to triaxial tests through the critical state models. Author: Fed. Univ. Rio de Janeiro, Brazil.

Lubkin, P. & M.A. Van (eds.) 90 5410 146 6

Building on soft soils – Design and construction of earth structures both on & into highly compressible subsoils of low bearing capacity May 1995, 25 cm, c.500 pp., Hfl.185/\$95.00/£69

A practical comprehensive manual treating all aspects of this subject. From the pre-design stage up to actual use (including maintenance) of the completed structures. 6 appendices treat particular aspects of interest from the preceding chapters. Text compiled by researchers from Fugro, Delft Geotechnics & other Dutch contractors.

Sorokina, G.V. 90 5410 236 5

Engineering properties of weak soils at foundations of buildings (Geotechnika 12 – Selected translations of Russian geotechnical literature)

1995, 24 cm, 222 pp., Hfl.150/\$85.00/£55 (No rights India)

Methods for investigating poorly lithified soils under field and laboratory conditions. Provides also laws governing the deformation of such soils under loading in terms of non-linear relationships. Examples have been given to illustrate the method of determining viscoplastic flow and strength of soils as a function of time.

Biares, J. & P.Y.Hicher 90 5410 156 3

Elementary mechanics of soil behaviour

Saturated remoulded soils

1994, 25 cm, 184 pp., Hfl.95/\$55.00/£35

(Student edn., 90 5410 157 1, Hfl.65/\$35.00/£24)

Treats fundamental behaviour of granular materials ranging from clays to road aggregates. Shows how observed properties can be classified and correlated for use in determining parameters for constitutive laws. *Contents:* Mechanics of particular media; Continuity hypothesis; Compression tests; Normally consolidated behaviour; Overconsolidated behaviour; Oedometer path; Classification of and correlations between the parameters; Three-dimensional behaviour - Effect of the intermediate principal stress; Anisotropy; Cyclic behaviour of soils. Authors: Ecole Centrale de Paris, France.

Shvets, V.B. 90 5410 235 7

Construction of structures on eluvial soils (Geotechnika 11 – Selected translations of Russian geotechnical literature)

1994, 24 cm, 210 pp., Hfl.125/\$70.00/£46 (No rights India)

The eluvial soils often found at sites of construction consist of the products of weathering & their strength & deformation properties vary widely (from fissured rocks to loose sands & fine clayey soils). The physical & mechanical properties of eluvial soils are examined. Modern methods of evaluating degree of weathering, deformation & strength characteristics as well as frost heave in such soils are described. Problems of design of foundations on eluvial soils of various degrees of weathering, from jointed rock to loose sand and silt-clay formations, are highlighted.

Publications Committee XIII ICSMFE (eds.) 90 5410 370 1

Proceedings of the thirteenth international conference on soil mechanics and foundations engineering, New Delhi, 5-10

January 1994 / Comptes-rendus du treizième congrès international de mécanique des sols et des travaux de fondations, New

Delhi, 5-10 janvier 1994 (No rights India)

1994-95, 28 cm, c.3500 pp., 6 vols, Hfl.1350/\$750.00/£500

The most important conference on soil mechanics & foundation engineering, held every four years. All papers were selected and reviewed by the national societies of the ISSMFE. Nearly all papers in English. Soil properties; Foundations; Design & performance of retaining & buried structures; Embankment dams & dam foundations; Natural hazard mitigation; Ground improvement; Liquefaction; Geophysical methods; Professional practices; Computer applications; Foundations of old structures & monuments; etc.

Katti, R.K. & A.R.Katti 90 5410 266 7

Behaviour of saturated expansive soil and control methods

1994, 24 cm, 1100 pp., Hfl.175/\$95/£65 (No rights India)

Properties. Conventional & insitu properties; Swelling pressure and heave. *Shear strength.* Studies; Studies with CNS surcharge. *Earth pressure behaviour.* Investigation on MRBC 76 soil for K_0 condition; Studies on MRBC 37 soil system for K_0 condition with additional instrumentation; Lateral pressure development under K_0 condition; Development of mathematical relations based on cohesion concept; Lateral pressure under K_p conditions. *Load bearing aspects.* With & without CNS & MSM. *Soil improvement. Mechanics. Guidelines.* Lining of canals in expansive soil. *Case histories.*

Bergado, D.T., J.C.Chai, M.C.Alfaro & A.S.Balasubramaniam

Improvement techniques of soft ground in subsiding and lowland environment

1994, 25 cm, 232 pp., Hfl.165/\$95.00/£61 90 5410 144 X

(Student edn., 90 5410 153 9, Hfl.95/\$55.00/£35)

Outlined, for the first time, are the problems commonly encountered during infrastructure constructions on soft and subsiding ground in lowland environments and their solutions in terms of soil/ground improvement techniques. *Contents:* Ground improvement by vertical drains; Ground improvement using granular piles; Lime/cement deep mixing method; Mechanically stabilized earth (MSE) embankment/walls; Conclusions; References. Authors: AIT, Bangkok.

Haan, E.den, R.Termaat & T.B.Edil (eds.) 90 5410 366 3

Advances in understanding and modelling the mechanical behaviour of peat – Proceedings of the international workshop, Delft, Netherlands, 16-18 June 1993

1994, 25 cm, 440 pp., Hfl.180/\$105.00/£67

Peat is one of the most compressible soils in nature. Whenever possible, geotechnical engineers will avoid this difficult material by building elsewhere, or removing it completely from underneath their structures. *Topics:* One-dimensional behaviour; Stress-strain & strength behaviour; Immediate issues in engineering practice.

Shibuya, S., T.Mitachi & S.Miura (eds.) 90 5410 399 X

Pre-failure deformation of geomaterials – Proceedings of the international symposium on pre-failure deformation characteristics of geomaterials, Sapporo, Japan, 12-14 September 1994

1994-95, 25 cm, c.1200 pp., 2 vols, Hfl.240/\$135.00/£88

World-wide experiences and new developments on the measurement and application of shear deformation characteristics of a wide spectrum of geomaterials: Clays, sands, gravels, soft rocks and cement-treated soils. Papers in Volume 1 have been devoted to the subjects on: Measurement of shear deformation of geomaterials in both laboratory and field tests; Modelling of shear deformation of geomaterials and Prediction, performance and design. The state-of-the-art in this field is summarized in Volume 2, which includes invited papers offered by internationally distinguished scholars.

All books available from your bookseller or directly from the publisher:

A.A. Balkema Publishers, P.O. Box 1675, Rotterdam, Netherlands

For USA & Canada: A.A. Balkema Publishers, Old Post Rd, Brookfield, VT, USA